




ROMET

Rotary Gas Meters



METER SIZE	ANSI 125 FF FLANGE	A	B	C	D1	D2	D3	D4	D5	D6	E1	E2	WEIGHT (lbs)
RM650	4"	9.50"	Ø 9.0"	11.84"	27.52"	28.94"	29.78"	30.72"	30.25"	30.31"	4.00"	4.00"	74-84

RM650 - SOFT METRIC


SOFT METRIC RM650 4" FLANGE CONNECTION

TECHNICAL SPECIFICATION

Connection (Flange)	ANSI 125FF	4"
MAOP	(kPa)	1206
Flow Capacity	(m ³ /h)	650
Rangeability @ ± 1% Error		75:1
Rangeability @ ± 2% Error		160:1
Start Rate	(m ³ /h)	.495
Stop Rate	(m ³ /h)	.340
Differential @ 100% Flow	(Pa)	597
Instrument Drive Rate	(m ³ /rev)	1.0
LF Pulsar (Optional on Std Ctr)	(m ³ /pulse)	1.0

CORRECTED FLOW CAPACITY AND TYPICAL ACCURACY GUIDE

RM650 METER (SM ³ /H)	
Gauge Pressure kPa 1.72	RM650 Qmax = 650 m ³ /hr
5	680.0
10	712.1
50	968.6
100	1289.4
150	1610.0
200	1930.9
250	2251.6
300	2572.4
500	3855.4
750	5459.2
1000	7062.9
1100	7704.4
1200	8345.9



ROMET

GAS METERS AND ELECTRONIC INSTRUMENTS
 Phone 905-624-1591 USA 1-800-387-3201
 www.rometlimited.com • email: romet@rometlimited.com

The values quoted are typical of normal production. They do not constitute a specification. Romet Limited reserves the right to change any information in this literature without notice. All of the information and data in this literature has been carefully compiled and thoroughly checked. However, Romet Limited will not assume responsibility for any possible omissions or errors.
 ROMET and ROMET & DESIGN are registered trademarks of Romet Limited. Romet Limited's gas metering technology is protected under U.S. Patent No. 4,910,519 and 6,453,721 and Canadian Patent No. 1,293,568.